



JCS3AN150A

主要参数 MAIN CHARACTERISTICS

ID	3 A
VDSS	1500 V
Rdson-max (@Vgs=10V))	8.0 Ω
Qg-typ	37nC

用途

- 高频开关电源
- 电子镇流器
- UPS 电源

APPLICATIONS

- High efficiency switch mode power supplies
- Electronic lamp ballasts based on half bridge
- UPS









产品特性

- 低栅极电荷
- 低 C_{RSS} (典型值 29pF)
- 开关速度快
- 产品全部经过雪崩测试
- 高抗 dv/dt 能力
- RoHS 产品

FEATURES

- Low gate charge
- Low C_{RSS} (typical 29pF)
- Fast switching
- 100% avalanche tested
- Improved dv/dt capability
- RoHS product

封装 Package



**订货信息 ORDER MESSAGE**

订 货 型 号 Order codes				印 记 Marking	封 装 Package
有卤-条管 Halogen-Tube	无卤-条管 Halogen-Free-Tube	有卤-编带 Halogen-Reel	无卤-编带 Halogen-Free-Reel		
JCS3AN150CA-C-B	JCS3AN150CA-C-BR	N/A	N/A	JCS3AN150CA	TO-220C
JCS3AN150FA-F-B	JCS3AN150FA-F-BR	N/A	N/A	JCS3AN150FA	TO-220MF
JCS3AN150AA-A-B	JCS3AN150AA-A-BR	N/A	N/A	JCS3AN150AA	TO-3P(H)IS
JCS3AN150WA-W-B	JCS3AN150WA-W-BR	N/A	N/A	JCS3AN150WA	TO-247
N/A	JCS3AN150SA-S-BR	N/A	JCS3AN150SA-S-AR	JCS3AN150SA	TO-263
N/A	JCS3AN150BA-B-BR	N/A	N/A	JCS3AN150BA	TO-262
N/A	JCS3AN150SLA-SL-BR	N/A	JCS3AN150SLA-SL-AR	JCS3AN150SLA	TO-263-2L



绝对最大额定值 ABSOLUTE RATINGS ($T_c=25^{\circ}\text{C}$)

项 目 Parameter	符 号 Symbol	数 值 Value			单 位 Unit
		JCS3AN150 CA/BA/SA/SLA	JCS3AN150 AA	JCS3AN150 FA	
最高漏极-源极直流电压 Drain-Source Voltage	V_{DSS}	1500			V
连续漏极电流 Drain Current -continuous	I_{D} $T=25^{\circ}\text{C}$ $T=100^{\circ}\text{C}$	3*			A
		1.8*			A
最大脉冲漏极电流 (注 1) Drain Current -pulse (note 1)	I_{DM}	12*			A
最高栅源电压 Gate-Source Voltage	V_{GS}	± 30			V
单脉冲雪崩能量 Single Pulsed Avalanche Energy	E_{AS}	460			mJ
雪崩电流 (注 1) Avalanche Current (note 1)	I_{AR}	3			A
耗散功率 Power Dissipation	P_{D} $T_c=25^{\circ}\text{C}$ -Derate above 25°C	368	69	48	W
最高结温及存储温度 Operating and Storage Temperature Range	$T_{\text{J}}, T_{\text{STG}}$	$-55 \sim +150$			$^{\circ}\text{C}$
引线最高焊接温度 Maximum Lead Temperature for Soldering Purposes	T_{L}	300			$^{\circ}\text{C}$

*漏极电流由最高结温限制

*Drain current limited by maximum junction temperature





电特性 ELECTRICAL CHARACTERISTIC

项 目 Parameter	符 号 Symbol	测试条件 Tests conditions	最小 Min	典型 Typ	最大 Max	单 位 Units
关态特性 Off –Characteristics						
漏—源击穿电压 Drain-Source Voltage	BV_{DSS}	$I_D=250\mu A$, $V_{GS}=0V$	1500	-	-	V
击穿电压温度特性 Breakdown Voltage Temperature Coefficient	$\Delta BV_{DSS} / \Delta T_J$	$I_D=250\mu A$, referenced to $25^\circ C$	-	0.5	-	V/ $^\circ C$
零栅压下漏极漏电流 Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=1500V$, $V_{GS}=0V$, $T_C=25^\circ C$	-	-	10	μA
		$V_{DS}=1500V$, $T_C=125^\circ C$	-	-	500	μA
正向栅极体漏电流 Gate-body leakage current, forward	I_{GSSF}	$V_{DS}=0V$, $V_{GS}=30V$	-	-	100	nA
反向栅极体漏电流 Gate-body leakage current, reverse	I_{GSSR}	$V_{DS}=0V$, $V_{GS}=-30V$	-	-	-100	nA
通态特性 On-Characteristics						
阈值电压 Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}$, $I_D=250\mu A$	3.0	-	5.0	V
正向跨导 Forward Transconductance	g_{fs}	$V_{DS} = 30V$, $I_D=3$ (note 3)	-	5.8	-	S
静态导通电阻 Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS} = 10V$, $I_D=1.5A$	-	6.3	8	Ω
动态特性 Dynamic Characteristics						
输入电容 Input capacitance	C_{iss}	$V_{DS}=25V$, $V_{GS}=0V$, $f=1.0MHz$	-	824	-	pF
输出电容 Output capacitance	C_{oss}		-	127	-	pF
反向传输电容 Reverse transfer capacitance	C_{rss}		-	29	-	pF





电特性 ELECTRICAL CHARACTERISTICS

项 目 Parameter	符 号 Symbol	测试条件 Tests conditions	最小 Min	典型 Typ	最大 Max	单位 Units
开关特性 Switching –Characteristics						
延迟时间 Turn-On delay time	t _d (on)	V _{DD} =750V, I _D =3A, R _G =4.7Ω（note 3, 4）	-	31	-	ns
上升时间 Turn-On rise time	t _r		-	56	-	ns
延迟时间 Turn-Off delay time	t _d (off)		-	105	-	ns
下降时间 Turn-Off Fall time	t _f		-	115	-	ns
栅极电荷总量 Total Gate Charge	Q _g	V _{DS} =750V ,	-	37	-	nC
栅—源电荷 Gate-Source charge	Q _{gs}	I _D =3A	-	6	-	nC
栅—漏电荷 Gate-Drain charge	Q _{gd}	V _{GS} =10V（note 3, 4）	-	22	-	nC
漏—源二极管特性及最大额定值 Drain-Source Diode Characteristics and Maximum Ratings						
正向最大连续电流 Maximum Continuous Drain-Source Diode Forward Current	I _S		-	-	3	A
正向最大脉冲电流 Maximum Pulsed Drain-Source Diode Forward Current	I _{SM}		-	-	12	A
正向导通压降 Forward on voltage	V _{SD}	V _{GS} =0V, I _S =/ 3A	-		1.6	V
反向恢复时间 Reverse recovery time	t _{rr}	V _{GS} =0V, I _S =3A, dl _F /dt=100A/μs (note 3)		376		ns
反向恢复电荷 Reverse recovery charge	Q _{rr}			2.1		μC

热特性 THERMAL CHARACTERISTIC



项 目 Parameter	符 号 Symbol	最大值 Value			单 位 Unit
		JCS3AN150 CA/BA/SA/SLA	JCS3AN150 AA	JCS3AN150 FA	
结到管壳的热阻 Thermal Resistance, Junction to Case	$R_{th(j-c)}$	0.34	1.8	2.6	$^{\circ}C/W$
结到环境的热阻 Thermal Resistance, Junction to Ambient	$R_{th(j-A)}$	62.5	40	62.5	$^{\circ}C/W$






特征曲线 ELECTRICAL CHARACTERISTICS (curves)


Capacitance Characteristics

On-Resistance Variation vs. I_D 


Maximum Safe Operating Area for JCS3AN150CA/BA/SA/SLA




Thermal impedance for JCS3AN150CA/BA/SA/SLA



Maximum Safe Operating Area for JCS3AN150AA




Thermal impedance for JCS3AN150AA






特征曲线 ELECTRICAL CHARACTERISTICS (curves)


Maximum Safe Operating Area for JCS3AN150FA




Thermal impedance for JCS3AN150FA




Output characteristics




Transfer characteristics



Normalized BVdss vs. temperature






Gate charge vs. Vgs







特征曲线 ELECTRICAL CHARACTERISTICS (curves)

Normalized V_{TH} vs. temperatureNormalized V_{SD} vs. temperatureMaximum Drain Current vs.
Case Temperature



TO-3P(H)IS


单位 Unit : mm



符 号 Symbol	Min	Max
A	5.2	5.8
B1	1.8	2.2
b	0.75	1.05
c	0.8	1.1
D	24.0	25.0
D1	9.8	10.2
E	15.0	16.0
e	5.45 (typ)	
F	2.7	3.3
L	18.5	19.5
L1	1.8	2.2
L2	4.3	4.7
ΦP	3.4	3.8
Q	4.3	4.7
Q1	3.1	3.5




TO-247



符号 symbol	MIN	MAX
A	4.90	5.10
B	2.95	3.35
B1	1.95	2.35
b	1.15	1.35
c	0.50	0.70
D	20.90	21.10
E	15.70	15.90
e	5.34	5.54
F	1.90	2.10
L	19.40	20.40
L2	4.03	4.23
Q	6.00	6.40
Q1	2.30	2.50
P	3.50	3.70



TO-220C




符号 symbol	MIN	MAX
A	4.30	4.70
B	1.22	1.40
b	0.70	0.95
c	0.40	0.65
D	15.20	16.20
D2	9.00	9.40
E	9.70	10.10
e	2.39	2.69
F	1.25	1.40
L	12.60	13.60
L2	2.80	3.20
Q	2.60	3.00
Q1	2.20	2.60
P	3.50	3.80





TO-220MF




SYMBOL	mm	
	MIN	MAX
A	4.5	4.9
B	1.22	1.47
b	0.7	0.9
c	0.45	0.60
D	15.6	16.1
D1	9.0	9.3
e	2.54TYPE	
E	9.9	10.4
F	2.3	2.8
L	12.6	13.3
L1	3.1	3.4
Q	3.2	3.4
Q1	2.6	2.9
ΦP	3.0	3.5





TO-262





符号 symbol	MIN	MAX
A	4.40	4.90
B	1.10	1.40
b	0.70	0.95
c	0.30	0.60
c1	0.33	0.63
D2	8.20	9.20
E	9.60	10.50
e	2.39	2.69
F	1.20	1.35
L	13.11	14.61
L2	3.55	4.05
Q	1.10	1.40
Q1	2.65	2.85








外形尺寸 PACKAGE MECHANICAL DATA

TO-263



SYMBOL	MM	
	MIN	MAX
A	4.30	4.80
A1	1.12	1.42
A2	2.54	2.84
b	0.67	1.00
c	0.29	0.52
D1	8.40	9.00
E	9.80	10.46
e	2.54BSC	
H	14.00	16.00
H2	1.12	1.45
L	1.50	3.10
L1	1.45	1.70


编带 REEL



产品尺寸规格 (UNIT: mm)				
规格 W	A0	E	F	D
尺寸 24 ± 0.3	10.9 ± 0.1	1.75 ± 0.1	11.5 ± 0.1	$1.5 +0.1/-0$
规格 D1	P0	P2	P	T
尺寸 $1.5 +0.1/-0$	4 ± 0.1	2 ± 0.1	16 ± 0.1	0.35 ± 0.05
规格 K0	B0			
尺寸 4.9 ± 0.1	16.0 ± 0.1			



TO-263-2L



SYMBOL	MM	
	MIN	MAX
A	4.18	4.68
A1	1.10	1.50
A2	2.40	2.80
b	0.63	1.00
c	0.35	0.70
D1	8.80	9.40
E	9.88	10.48
e	5.08 BSC	
H	14.50	16.50
H1	0.95	1.45
L	1.70	2.70





注意事项

1. 吉林华微电子股份有限公司的产品销售分为直销和销售代理，无论哪种方式，订货时请与公司核实。
2. 购买时请认清公司商标，如有疑问请与公司本部联系。
3. 在电路设计时请不要超过器件的绝对最大额定值，否则会影响整机的可靠性。
4. 本说明书如有版本变更不另外告知。

NOTE

1. Jilin Sino-microelectronics co., Ltd sales its product either through direct sales or sales agent , thus, for customers, when ordering , please check with our company.
2. We strongly recommend customers check carefully on the trademark when buying our product, if there is any question, please don't be hesitate to contact us.
3. Please do not exceed the absolute maximum ratings of the device when circuit designing.
4. Jilin Sino-microelectronics co., Ltd reserves the right to make changes in this. specification sheet and is subject to change without prior notice.

联系方式

吉林华微电子股份有限公司

公司地址：吉林省吉林市深圳街 99 号

邮编：132013

总机：86-432-64678411

传真：86-432-64665812

网址：www.hwdz.com.cn

CONTACT

JILIN SINO-MICROELECTRONICS CO., LTD.

ADD: No.99 Shenzhen Street, Jilin City, Jilin Province, China.

Post Code: 132013

Tel: 86-432-64678411

Fax: 86-432-64665812

Web Site: www.hwdz.com.cn

