



JT020N065SED/CED/WED/FED

主要参数 MAIN CHARACTERISTICS

I_C	20 A
BV_{CES}	650V
$V_{CESAT-typ}$ ($V_{GE}=15V$)	1.6V

用途

- 逆变器
- UPS 电源

APPLICATIONS

- General purpose inverters
- UPS



产品特性

- 低栅极电荷
- Trench FS 技术,
- 通态压降, $V_{CE(sat)}$, $typ = 1.6V, I_C = 20A$ and $T_C = 25^\circ C$
- RoHS 产品


FEATURES

- Low gate charge
- Trench FS Technology,
- saturation voltage: $V_{CE(sat)}$, $typ = 1.6V, I_C = 20A$ and $T_C = 25^\circ C$
- RoHS product

封装 Package




TO-263



TO-220C



TO-247



TO-220MF

订 货 型 号 Order codes				印 记 Marking	封 装 Package
有卤-条管 Halogen-Tube	无卤-条管 None Halogen-Tube	有卤-编带 Halogen-Reel	无卤-编带 Halogen-Free-Reel		
JT020N065SED-S-B	JT020N065SED-S-BR	JT020N065SED-S-A	JT020N065SED-S-AR	JT020N065SED	TO-263
JT020N065CED-C-B	JT020N065CED-C-BR	N/A	N/A	JT020N065CED	TO-220C
JT020N065WED-GE-B	JT020N065WED-GE-BR	N/A	N/A	JT020N065WED	TO-247
JT020N065FED-F-B	JT020N065FED-F-BR	N/A	N/A	JT020N065FED	TO-220MF



绝对最大额定值 ABSOLUTE RATINGS ($T_c=25^{\circ}\text{C}$)

项 目 Parameter	符 号 Symbol	数 值 Value			单 位 Unit
		JT020N065SED/ JT020N065CED	JT020N065WED	JT020N065FED	
最高集电极—发射极直流 电压 Collector-Emmitter Voltage	V _{CES}	650	650	650	V
*连续集电极电流 Collector Current-continuous	I _C	40 (T _C =25℃)	40 (T _C =25℃)	40 (T _C =25℃)	A
		20(T _C =100℃)	20(T _C =100℃)	20(T _C =100℃)	A
最大脉冲集电极极电流（注 1） Collector Current – pulse （note 1）	I _{CM}	80	80	80	A
二极管正向测试电流 Diode RMS forward current	I _F	40(T _C =25℃)	40(T _C =25℃)	40(T _C =25℃)	A
	I _F	20(T _C =100℃)	20(T _C =100℃)	20(T _C =100℃)	A
二极管正向不重复峰值电 流（浪涌电流） Surge non repetitive forward current tp= 10 ms sinusoidal	I _{FSM}	80	80	80	A
最高栅极发射极电压 Gate-Emmitter Voltage	V _{GES}	±20	±20	±20	V
Turn-off safe area	-	80	80	80	A
耗散功率 Power Dissipation	P _D T _C =25℃	187	194	42	W
存储温度 Storage Temperature Range	T _{STG}	-55～+150	-55～+150	-55～+150	℃
结温 Operating Temperature Range	T _J	-55～+175	-55～+175	-55～+175	℃
引线最高焊接温度 Maximum Lead Temperature for Soldering Purposes	T _L	300	300	300	℃

*连续集电极电流由最高结温限制

*Collector current limited by maximum Junction temperature





电特性 ELECTRICAL CHARACTERISTICS

项 目 Parameter	符 号 Symbol	测试条件 Tests conditions	最小 Min	典型 Typ	最大 Max	单位 Units
关态特性 Off –Characteristics						
集电极—发射极击穿电压 Collector-Emmitter Voltage	BV _{CES}	I _C =500μA, V _{GE} =0V	650	-	-	V
击穿电压温度特性 Breakdown Voltage Temperature Coefficient	ΔBV _{CES} /ΔT _J	I _C =1mA, referenced to 25°C	-	0.5	-	V/°C
零栅压下集电极漏电流 Zero Gate Voltage Collector Current	I _{CES}	V _{CE} =650V, V _{GE} =0V, T _C =25°C	-	-	10	μ A
正向栅极体漏电流 Gate-body leakage current, forward	I _{GESF}	V _{CE} =0V, V _{GE} =20V	-	-	200	nA
反向栅极体漏电流 Gate-body leakage current, reverse	I _{GESR}	V _{CE} =0V, V _{GE} =-20V	-	-	-200	nA
通态特性 On-Characteristics						
阈值电压 Gate Threshold Voltage	V _{GE(th)}	V _{CE} = V _{GE} , I _C =250μA	5.5	-	6.5	V
饱和压降 Collector-Emmitter saturation Voltage	V _{CESAT}	V _{GE} =15V, I _C =20A, T _c =25°C	-	1.6	2.0	V
		V _{GE} =15V, I _C =20A, T _c =125°C		1.75	2.15	V
		V _{GE} =15V, I _C =20A, T _c =175°C		1.9	2.3	V
动态特性 Dynamic Characteristics						
输入电容 Input capacitance	C _{ies}	V _{CE} =25V, V _{GE} =0V, f=1.0MHz, T _C =25°C	-	1500	-	pF
输出电容 Output capacitance	C _{oes}		-	128	-	pF
反向传输电容 Reverse transfer capacitance	C _{res}		-	28.7	-	pF
栅极电荷总量 Total Gate Charge	Q _g	V _{CC} =400V, I _C =20A, R _G =10Ω, V _{GE} =15V, T _C =25°C	-	43.9	-	nC
栅极-发射极 Gate to emitter charge	Q _{ge}		-	10.0	-	
栅极-集电极 Gate to collector charge	Q _{gc}		-	18.9	-	
栅极电阻-Gate resistance	R _g	f=1MHz, open collector	-	1.8	-	Ω
短路电流-short current	I _{sc}	V _{GE} =15V, V _{CE} =360V, T _{Jstart} ≤175°C, t≤10μs	-	106	-	A





电特性 ELECTRICAL CHARACTERISTICS

开关特性 Switching Characteristics						
项 目 Parameter	符 号 Symbol	测试条件 Tests conditions	最小 Min	典型 Typ	最大 Max	单位 Units
开启延迟时间 Turn-On delay time	t _{d(on)}	V _{CC} =400V,I _{CC} =20A, R _G =10Ω, V _{GE} =15V, T _C =25°C	-	16	-	ns
上升时间 Turn-On rise time	t _r		-	56	-	ns
关断延迟时间 Turn-Off delay time	t _{d(off)}		-	52	-	ns
下降时间 Turn-Off Fall time	t _f		-	82	-	ns
开通损耗 Turn-On energy	E _{on}		-	0.79	-	mJ
关断损耗 Turn-off energy	E _{off}		-	0.3	-	mJ
总开关损耗 Total switching energy	E _{tot}		-	1.09	-	mJ
开启延迟时间 Turn-On delay time	t _{d(on)}	V _{CC} =400V,I _C =20A, R _G =10Ω,V _{GE} =15V, T _C =175°C	-	14.0	-	ns
上升时间 Turn-On rise time	t _r		-	54.0	-	ns
关断延迟时间 Turn-Off delay time	t _{d(off)}		-	76.0	-	ns
下降时间 Turn-Off Fall time	t _f		-	146.0	-	ns
开通损耗 Turn-On energy	E _{on}		-	0.8	-	mJ
关断损耗 Turn-off energy	E _{off}		-	0.49	-	mJ
总开关损耗 Total switching energy	E _{tot}		-	1.3	-	mJ
反并联二极管特性及最大额定值 Anti-Parallel Diode Characteristics and Maximum Ratings						
正向压降 Drain-Source Diode Forward Voltage	V _F	V _{GE} =0V, I _F =20A,T _C =25°C	-	1.6	-	V
		V _{GE} =0V, I _F =20A,T _C =125°C	-	1.4	-	V
		V _{GE} =0V, I _F =20A,T _C =175°C	-	1.3	-	V
反向恢复时间 Diode Reverse recovery time	t _{rr}	T _C =25°C,I _F =20A, V _{GE} =0V,d _i /d _t =100A/us	-	254	-	ns
反向恢复电荷 Diode Reverse recovery charge	Q _{rr}		-	347	-	nC
反向恢复电流 Diode Reverse recovery Current	I _{rrm}		-	2.7	-	A
反向恢复时间 Diode Reverse recovery time	t _{rr}	T _C =175°C, I _F =20A, V _{GE} =0V,d _i /d _t =100A/us	-	429	-	ns
反向恢复电荷 Diode Reverse recovery charge	Q _{rr}		-	1010	-	nC
反向恢复电流 Diode Reverse recovery Current	I _{rrm}		-	4	-	A











JT020N065SED/CED/WED/FED







项目 Parameter	符号 Symbol	最大 (max)			单位 Unit
		JT020N065SED/ JT020N065CED	JT020N065WED	JT020N065FED	
结到管壳的热阻 (IGBT) Thermal Resistance, Junction to Case	$R_{th(J-C)}$	0.8	0.77	3.57	°C/W
结到管壳的热阻 (FRD) Thermal Resistance, Junction to Case	$R_{th(J-C)}$	2.13	2.05	7.7	°C/W
结到环境的热阻 Thermal Resistance, Junction to Ambient	$R_{th(J-A)}$	62.5	40	62.5	°C/W














特征曲线 ELECTRICAL CHARACTERISTICS (curves)


Output Characteristics $T_J=25^\circ\text{C}$ Output Characteristics $T_J=175^\circ\text{C}$ Transfer characteristics $V_{CE}=6\text{V}$ 归一化的 V_{GE} 与 T_J 关系曲线归一化的 BV_{CE} 与 T_J 关系曲线 I_c VS T_c 

 **V_{CESAT} VS T_J**  **V_{CESAT} VS I_C** **Capacitance Characteristic** **$V_{GE}=0V, f=1.0MHz$**  **Q_g VS V_{GE}** **SwitchingTime vs. I_C** **$T_J=25^{\circ}C, V_{GE}=15V, V_{CE}=400V, R_g=10\Omega$** **SwitchingTime vs. I_C** **$T_J=175^{\circ}C, V_{GE}=15V, V_{CE}=400V, R_g=10\Omega$** 


Switching Time vs. R_g $T_J=25^{\circ}\text{C}, V_{GE}=15\text{V}, V_{CE}=400\text{V}, I_C=20\text{A}$ Switching Time vs. R_g $T_J=175^{\circ}\text{C}, V_{GE}=15\text{V}, V_{CE}=400\text{V}, I_C=20\text{A}$ Switching Time vs. T_J Switching Loss vs. I_C $T_J=25^{\circ}\text{C}, V_{GE}=15\text{V}, V_{CE}=400\text{V}, R_g=10\Omega$ Switching Loss vs. I_C $T_J=175^{\circ}\text{C}, V_{GE}=15\text{V}, V_{CE}=400\text{V}, R_g=10\Omega$ Switching Loss vs. R_g $T_J=25^{\circ}\text{C}, V_{GE}=15\text{V}, V_{CE}=400\text{V}, I_C=20\text{A}$ 

Switching Loss vs. R_g $T_J=175^{\circ}\text{C}, V_{GE}=15\text{V}, V_{CE}=400\text{V}, I_C=20\text{A}$ Switching Loss vs. T_J $V_{GE}=15\text{V}, V_{CE}=400\text{V}, I_C=20\text{A}, R_g=10\Omega$ Switching Loss vs. $V_{CE}(V)$ $T_J=175^{\circ}\text{C}, V_{GE}=15\text{V}, I_C=20\text{A}, R_g=10\Omega$ 


Safe Operating Area TO-247











Safe Operating Area TO-263/TO-220C




Safe Operating Area TO-220MF




**P_D VS temperature (TO-263/TO-220C)****P_D VS temperature (TO-247)****P_D VS temperature (TO-220MF)****Diode Characteristic****T_{rr}与dI/dt关系曲线****Q_{rr}与dI/dt关系曲线**

 E_{rr} 与 d_i/d_t 关系曲线 I_{rrm} 与 d_i/d_t 关系曲线


Normalized Maximum Transient Thermal Impedance for IGBT(TO-247)



Normalized Maximum Transient Thermal Impedance for IGBT(TO-263/TO-220C)



Normalized Maximum Transient Thermal Impedance for IGBT(TO-220MF)






外形尺寸PACKAGE MECHANICAL DATA

TO-263

单位 UNIT:mm



SYMBOL	MM	
	MIN	MAX
A	4.30	4.80
A1	1.12	1.42
A2	2.54	2.84
b	0.67	1.00
c	0.29	0.52
D1	8.40	9.00
E	9.80	10.46
e	2.54BSC	
H	14.00	16.00
H2	1.12	1.45
L	1.50	3.10
L1	1.45	1.70






外形尺寸PACKAGE MECHANICAL DATA

TO-247

单位 UNIT:mm



符号 symbol	MIN	MAX
A	4.90	5.10
B	2.95	3.35
B1	1.95	2.35
b	1.15	1.35
c	0.50	0.70
D	20.90	21.10
E	15.70	15.90
e	5.34	5.54
F	1.90	2.10
L	19.40	20.40
L2	4.03	4.23
Q	6.00	6.40
Q1	2.30	2.50
P	3.50	3.70






外形尺寸PACKAGE MECHANICAL DATA

TO-220MF

单位 UNIT:mm



SYMBOL	mm	
	MIN	MAX
A	4.5	4.9
B		1.47
b	0.7	0.9
c	0.45	0.60
D	15.67	16.07
D1	9.04	9.20
e	2.54TYPE	
E	9.96	10.36
F	2.34	2.74
L	12.58	13.38
L1	3.13	3.33
Q	3.2	3.4
Q1	2.56	2.96
ΦP	3.08	3.28







外形尺寸PACKAGE MECHANICAL DATA

TO-220C

单位 UNIT:mm



符号 symbol	MIN	MAX
A	4.30	4.70
B	1.22	1.40
b	0.70	0.95
c	0.40	0.65
D	15.20	16.20
D2	9.00	9.40
E	9.70	10.10
e	2.39	2.69
F	1.25	1.40
L	12.60	13.60
L2	2.80	3.20
Q	2.60	3.00
Q1	2.20	2.60
P	3.50	3.80





注意事项

1. 吉林华微电子股份有限公司的产品销售分为直销和销售代理，无论哪种方式，订货时请与公司核实。
2. 购买时请认清公司商标，如有疑问请与公司本部联系。
3. 在电路设计时请不要超过器件的绝对最大额定值，否则会影响整机的可靠性。
4. 本说明书如有版本变更不另外告知。

NOTE

1. Jilin Sino-microelectronics co., Ltd sales its product either through direct sales or sales agent , thus, for customers, when ordering , please check with our company.
2. We strongly recommend customers check carefully on the trademark when buying our product, if there is any question, please don't be hesitate to contact us.
3. Please do not exceed the absolute maximum ratings of the device when circuit designing.
4. Jilin Sino-microelectronics co., Ltd reserves the right to make changes in this specification sheet and is subject to change without prior notice.

联系方式

吉林华微电子股份有限公司

公司地址：吉林省吉林市深圳街 99 号

邮编：132013

总机：86-432-64678411

传真：86-432-64665812

网址：www.hwdz.com.cn

市场营销部

地址：吉林省吉林市深圳街 99 号

邮编：132013

电话：86-432-64675588

64675688

64678411-3098/3099

传真：86-432-64671533

CONTACT

JILIN SINO-MICROELECTRONICS CO., LTD.

ADD: No.99 Shenzhen Street, Jilin City, Jilin Province, China.

Post Code: 132013

Tel: 86-432-64678411

Fax: 86-432-64665812

Web Site: www.hwdz.com.cn

MARKET DEPARTMENT

ADD: No.99 Shenzhen Street, Jilin City, Jilin Province, China.

Post Code: 132013

Tel: 86-432-64675588

64675688

64678411-3098/3099

Fax: 86-432-64671533

